



Complete Kit A.SCHILD®*-1900

Mechanical movement with Swiss pallet fork, direct sweep second, bevelled edges, 21 600 alternances/h, casing diameter 25,60 mm

100	Mainplate	440	Yoke spring
105	Barrel bridge	443	Setting lever
118	Combined bridge	445	Setting lever spring
121/3	Balance cock for stud holder and for shock-protecting device, flat hairspring	450	Setting wheel
125	Pallet cock	468	Cannon pinion guard
163/1	Center pipe	703	Escape wheel and pinion, for lower end-piece
182	Barrel and cover	710	Jewelled pallet fork and staff
195	Barrel arbor	714	Pallet staff
201/1	Large driving wheel	721	Balance with flat hairspring, regulated
210	Third wheel	728	Balance staff for shock-protecting device
227	Sweep second wheel	730	Roller
240	Cannon pinion with clam notch	770	Mainspring
243	Cannon pinion without clam notch	5102	Case screw
255	Hour wheel	5105	Barrel bridge screw
260	Timer wheel	5118	Combined bridge screw
307/1	Regulator for adjustable stud holder, for flat hairspring	5121	Balance cock screw
346	Lower cap jewel with end-piece, for esc. wheel	5125	Pallet cock screw
375	Adjustable stud holder, for flat hairspring	5346	Lower end-piece screw, for escape wheel
401	Winding stem	5415	Ratchet wheel screw
407	Clutch wheel	5420	Crown wheel screw
410	Winding pinion	5425	Click screw
415	Ratchet wheel	5443	Setting lever screw
420	Crown wheel	5445	Screw for setting lever spring
422	Crown wheel ring	5468	Screw for cannon pinion guard
425	Click	5738	Hairspring stud screw
430	Click spring	5750	Dial screw
435	Yoke		